



VANTAGE

FREE STANDING DIRECT VENT GAS STOVE

STYLING









CANNONBALLS















DECORATIVE EMBER GLASS

BRICK LINERS





HERRINGBONE (IDV43 ONLY)

TRADITIONAL





MQLOGF452 Oak Log Set, MQ453RLH Herringbone Brick Liner, F45FK Fan Kit.

Model **Gas Control** Fuel **Input High Input Low**

FE (P.4.1-02)

Glass

FDV451NE2 Millivolt / IPI Natural 34,500 BTU 23,750 BTU Single

FDV451N/NE 70.53/73.53% FDV451LP/LPE FDV451LPE2 Millivolt / IPI Propane 31,000 BTU 24,500 BTU 70.12 / 74.28% Single


MQFDV453N/NE MQFDV453NE2 Millivolt / IPI Natural 34,500 BTU 23,750 BTU 70.53 / 73.53%


Three

MQFDV453LP/LPE MQFDV453LPE2 Millivolt / IPI Propane 31,000 BTU 24,500 BTU 70.12 / 74.28% Three



OPTIONAL LOG GRATE PART #F45LG





MQFDV453 A 27 1/8" B 7" C 4" D 20" E 26" F 1 1/4" G 4" H 11 5/16" 16 15/16" 33 ¹/₂" K 20 ¹/8" $L = 5^{3/8}$ " M 15" N 10 5/8" O $19^{3}/4$ "

P 20 5/16"

Q 9/16"

MINIMUM CLEARANCES TO COMBUSTIBLES:

from front of unit $15^{1}/_{2}$ " from side of unit 2 ½" from back of unit

ALCOVE INSTALLATION:

depth (max.) 71 1/2" height (min.) width (min.)



Unit illustrated is a FDV451N Free Standing Stove -Natural Gas, F450FBL Door Front - Charcoal with Black Posts, F451SDSBL Side Doors - Solid Charcoal Panel with Black Frame, MQG5C Bronze Glass (x3), MQROCK3 Rock Set - Multi-Colored, F451RLT Traditional Brick Liner, F45FK Fan Kit.



Unit illustrated is the FDV451N Free Standing Direct Vent Stove - Natural Gas, F450FBL Door Front - Charcoal with Black Posts, F451SDFBL Side Doors - Flame Panel Charcoal - with Black Frame, MQG5C Bronze Glass (x3), RBCB1 Cannonballs, F45LG Log Grate, F45FK Fan Kit.



Unit illustrated is a MQFDV453N Free Standing Stove -Natural Gas, F450FBL Door Front - Charcoal with Black Posts, MQ453SDBL Side Doors with Black Frame and Charcoal Panel. MQG5C Bronze Glass (x3), MQSTONES Decorative Stones, MQ451RLH Herringbone Brick Liner, F45FK Fan Kit

STANDARD FEATURES

- > Dual burner system, with Realistic Flame Pattern.
- > Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment.
- > Heat radiating ceramic glass.
- > Mobile home approved.
- > Approved for installation in a bedroom or bed sitting room.
- > Proflame II Models include Remote Control -Features flame, fan, thermostat, smart thermostat, CPI/IPI cold climate control (FDV451NE2, FDV451LPE2, MQFDV453NE2 and MQFDV453LPE2 Models only).

OPTIONAL FEATURES

Fan Kit – Heat activated with variable speed control.

Three color choices – Charcoal with your choice of accent colour: Flat Black, Powder Coat Black, or Stainless, with matching side panels.

Media – with the following choices: Contemporary Rock, Decorative Stones and Decorative Ember Glass (Glacier Ice, Cobalt Blue, Black, Bronze and White) or Ember Chunks.

Log Sets - Driftwood or Oak Log Sets.

Refractory Brick Liner - Traditional, Herringbone or Black Fluted.

Porcelain Reflective Liner

Thermostat - Wall Mount Millivolt Thermostat or Programmable Thermostat.

Remote Control (Millivolt or IPI PF1) -Thermostat on/off, Thermostat on/off modulating, Thermostat on/off modulating and fan control.

* All gas fireplaces manufactured as of January 1, 2015 will include a Safety Screen Barrier.



POWDER COATED VENT LID



STAINLESS STEEL AND FLAT **BLACK VENT LID**



