



CAPELLA
SERIES 26
DIRECT VENT GAS FIREPLACE INSERT

TRIM OPTIONS

BLACK

PEWTER

VINTAGE COPPER VEIN

STYLING



ROCK COLLECTIO



DECORATIVE STONE



DECORATIVE EMBER GLASS

BRICK LINERS













IDV26N/NE IDV26/LPE Model **PROPANE** Fuel **NATURAL** 30,000 BTU 30,000 BTU Input Low 21,000 BTU 25,000 BTU **FE** (P.4.1-02) 65.3% 65.3%

MINIMUM FIREPLACE OPENING

| Ī | | WIDTH | HEIGHT | DEPTH | |
|---|--|----------|--------|---------|--|
| | IDV26 | 33"/28"* | 19 ½" | 14 1/4" | |
| | *Components In (CV1) 33", Components Out (CV2) 28" | | | | |

MINIMUM UNIT COVERAGE

| IDV26 | WIDTH | HEIGHT | | |
|--|-----------------------|---------------------|--|--|
| I26CV1 (Clean View-CV1)* I26CV2 (Clean View-CV2)* I26CV3 (Clean View-CV3)* | 34 ½" 41 ½" 34" | 22" 25 ½" 22" | | |
| *Back Frame Dimension of Clean View Kit | | | | |

CLEAN VIEW AND SURROUND SIZES

| IDV26 | WIDTH | HEIGHT | DEPTH | | | |
|--|----------------------------------|----------------------------------|---------------------------------|--|--|--|
| (Clean View Three Sided) | | | | | | |
| 126CV1 | 35 5/8" | 22 3/4" | 1 ³ / ₄ " | | | |
| 126CV2 | 44 5/8" | 26 5/8" | 1 ³ / ₄ " | | | |
| 126CV3 | 35 5/8" | 22 3/4" | 3 ½" | | | |
| (Clean View Picture Frame) | | | | | | |
| I26CVPF1 | 35 ⁵ / ₈ " | 25 ⁷ / ₈ " | | | | |
| I26CVPF2 | 44 1/8" | 33 ½" | | | | |
| (Surrounds - Three Sided) | | | | | | |
| I26S1 | 42" | 27 ½" | | | | |
| I26SU* | 47 1/2" | 28 5/8" | | | | |
| (Surrounds - Picture Frame) | | | | | | |
| I26SPF1 | 39 3/8" | 29 3/4" | | | | |
| I26SU* | 47 1/2" | 35 5/8" | | | | |
| *Universal Surround can be cut to size for custom application. | | | | | | |
| | | | | | | |

- 1. IDV26N Direct Vent Insert Natural Gas, MQLOGF26 Log Set, I26CVPF2BL Clean View Picture Frame - Black, IDV26RL Refractory Brick Liner.
- 2. IDV26N Direct Vent Insert Natural Gas, MQLOGF26 Log Set, I26CV3BL Clean View - Black, and IDV26RL Brick Liner.
- 3. IDV26N Direct Vent Insert Natural Gas, I26CV1CV Clean View -Copper Vein, MQLOGF26 Log Set, I26S1CV Surround – Copper Vein, IDV26RL Refractory Brick Liner.
- 4. IDV26N Direct Vent Insert Natural Gas, MQLOGF26 Log Set, I26CV1PW Clean View - Pewter, I26S1PW Surround - Pewter, IDV26RL Refractory Brick Liner.

STANDARD FEATURES*

- > Dual Burner with glowing embers and decorative ash bed
- > Millivolt valve system allows operation during power failure with adjustable flame control
- > Matchless Piezo Ignition
- > Heat radiating Ceramic Glass
- > On/Off Rocker switch
- > Heat activated blower with variable speed control
- > Safety Screen Barrier*



SAFETY SCREEN BARRIER

OPTIONAL FEATURES

Clean View Kit – Black, Pewter and Copper Vein

Picture Frame Clean View - Black, Pewter and Copper Vein

Surrounds – Black, Pewter and Copper Vein

Surrounds Picture Frame – Black, Pewter and Copper Vein

Contemporary Rock Collection* – Natural, or Multi-Coloured (Rock Support Platform required)

Decorative Stones or Ember Chunks

(Glass Support Platform required)

Decorative Ember Glass - Glacier Ice, White, Cobalt (Blue), or Bronze (Glass Support Platform required)

Log Set – Fibre Split Oak

Wall Mount Thermostat - Standard On/Off or Programmable

Remote Control - On/Off, Thermostat, **Modulating Thermostat**

Porcelain Reflective Liners

Brick Refractory Liner - Traditional



^{*} All gas fireplaces manufactured as of January 1, 2015 will include a Safety Screen Barrier.



